



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/781,792

02/20/2004

Tetsumei Tsuruoka

1341.1187

6392

21171 7590 08/16/2010  
STAAS & HALSEY LLP  
SUITE 700  
1201 NEW YORK AVENUE, N.W.  
WASHINGTON, DC 20005

EXAMINER

RICHARDSON, THOMAS W

ART UNIT

PAPER NUMBER

2444

MAIL DATE

DELIVERY MODE

08/16/2010

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

<b>Office Action Summary</b>	<b>Application No.</b> 10/781,792	<b>Applicant(s)</b> TSURUOKA ET AL.	
	<b>Examiner</b> THOMAS RICHARDSON	<b>Art Unit</b> 2444	

**-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --**

**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 25 July 2010.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-32 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-32 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |   |   |
|---|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)                    | 4) <input type="checkbox"/> Interview Summary (PTO-413)           |
| 2) <input type="checkbox"/> Notice of Draftperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____                                      |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)         | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____   | 6) <input type="checkbox"/> Other: _____                          |

### **DETAILED ACTION**

Claims 1-32 are pending for examination.

Claims 1, 2, 4, 6, 8, 10, 12, 14, 16, 18, 20, 23, 24, 27, 28, 31, and 32 are amended.

Claims 1-32 are rejected.

### ***Response to Arguments***

1. Applicant's arguments filed with respect to claims 1-32 have been fully considered but they are not persuasive. Applicant argues that cited references Foster (US 2003/0204618), Dalton (WO 99/14931), and Fink (US 6 496 935) do not teach the limitations of the claims.10781792

2. 10

3. Applicant argues with respect to claims 10, 11, 16, 17, 20, 24, 28, and 32 that neither Dalton nor Foster teaches newly added limitations of “deciding on, according to an algorithm prescribed by a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network; registering the path by the deciding to a routing table.” Applicant cites Foster as teaching a VI table for routing, and further states that the virtual identifier “identifies a path between devices.” However, Foster further teaches that the assignment of paths to such virtual path identifiers may be done dynamically (paragraph 16). As described, the path may be configured by the network manager such that each device in the path is configured between the source and destination. As such, the network manager exchanges information regarding a route with the packet forwarding device, and the packet is

Art Unit: 2444

forwarded based on information exchanged and set by the network manager, which is then set in the VI routing table to determine which interface is used to forward the packet. Thus, the previous rejection of claims 10, 11, 16, 17, 20, 24, 28, and 32 is maintained in view of Dalton and Foster.

4. Regarding claims 1, 2, 4, 6, 8, 12, 14, and 18, applicant makes similar arguments to those with respect to claim 10, in reference to the Foster reference. As such, examiner's comments with regard to claim 10 are similarly applicable.

5. Regarding claims 23, 27, and 31, applicant makes similar arguments to those with respect to claim 10, in reference to the Foster reference. As such, examiner's comments with regard to claim 10 are similarly applicable.

***Claim Rejections - 35 USC § 103***

6. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

7. Claims 10, 11, 16, 17, 20, 24, 28, and 32 are rejected under 35 U.S.C. 103(a) as being anticipated by US 2003/0204618, Foster et al and WO 99/14931, Dalton et al.

8. As per claim 10, Foster teaches a method of maintaining a routing table in a system that includes a packet forwarder and a packet control device, the packet forwarder including a plurality of network interfaces (Figure 2A, where each packet forwarder has multiple connection interfaces), the packet control device including a plurality of network interface and a plurality of virtual interfaces each of the virtual interfaces having address information that is associated with one of the network interfaces of the packet forwarder (paragraph [0029], where the virtual identifier

Art Unit: 2444

translation table reflects the IP ports related to the virtual interfaces of the VPN), the method comprising:

dividing the network interfaces of the packet control device and the virtual interfaces into a plurality of groups (Figures 2B and 2C, where the virtual and real addresses are kept separately and routed accordingly);

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

maintaining a routing table of each for the groups using a routing process associated with each of the groups (Figures 2B and 2C, where the virtual and real addresses are kept separately and routed accordingly).

Art Unit: 2444

Foster does not expressly teach that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Foster. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

9. As per claim 11, Foster further teaches wherein the virtual interfaces are grouped for each packet forwarder, further comprising maintaining a routing table of each packet forwarder using a routing process associated with each of the virtual interfaces grouped (Page 5, paragraph [0029], where each IFM maintains a virtual identifier table for each of its ports).

10. As per claim 16, Foster teaches a computer-readable storage for controlling a computer, comprising a computer program for maintaining a routing table (page 2, paragraph [0013], where the system is a software facility), the packet forwarder

Art Unit: 2444

including a plurality of network interfaces (Figure 2A, where each packet forwarder has multiple connection interfaces), the packet control device including a plurality of network interfaces and a plurality of virtual interfaces each of the virtual interfaces having address information that is associated with one of the network interfaces of the packet forwarder (page 5, paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN), the computer program including computer executable instructions which, when executed by the computer, cause the computer to perform:

- dividing the network interfaces of the packet control device and the virtual interfaces into a plurality of groups (Figures 2B and 2C, where the virtual and real addresses are kept separately and routed accordingly);

- deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

- registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

Art Unit: 2444

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

maintaining a routing table of each of the groups using a routing process associated with each of the groups (Figures 2B and 2C, where the virtual and real addresses are kept separately and routed accordingly).

Foster does not expressly teach that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Foster. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).



Art Unit: 2444

11. As per claim 17, Foster further teaches the virtual interfaces are grouped for each packet forwarder, and the instructions further cause the computer to perform maintaining a routing table of each packet forwarder using a routing process associated with each of the virtual interfaces grouped (Page 5, paragraph [0029], where each IFM maintains a virtual identifier table for each of its ports).

12. As per claim 20, Foster teaches a router control device (abstract, where the system processes received data for routing through a network) comprising:

a virtual interface setting unit that creates and manages virtual interfaces on a router control device according to corresponding network interfaces of a forwarder, each of the virtual interfaces having address information that is associated with one of the network interfaces of the forwarder (Page 5, paragraph [0029], where the IFM maintains a virtual identifier table for each of its ports);

a routing unit that generates a routing table for the forwarder based on routing information in routing information packets received at the network interface of the forwarder and transferred by the forwarder to the router control device (Figures 2B and 2C and accompanying description beginning page 5, paragraph [0032], where the device forms routing information tables according to the source and destination identifiers);

a deciding unit that decides on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device

Art Unit: 2444

in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

a registering unit that registers the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

a routing information storage unit that stores a routing table created and managed by the routing unit for packet forwarding between the virtual interfaces that are associated with an address of the virtual interface (Page 5, paragraph [0029], where each IFM contains a virtual identifier table for each of its ports).

Foster does not expressly teach that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Foster. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central

Art Unit: 2444

routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

13. As per claim 24, Foster teaches a method of maintaining a routing table (abstract), comprising:

creating and managing virtual interfaces on a router control device according to corresponding network interfaces of a forwarder, each of the virtual interfaces having address information that is associated with one of the network interfaces of the forwarder (Page 5, paragraph [0029], where the IFM maintains a virtual identifier table for each of its ports);

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

generating a routing table for the forwarder based on routing information in routing information packets received at the network interface of the forwarder and transferred by the forwarder to the router control device (Figures 2B and 2C and accompanying description beginning page 5, paragraph [0032], where the device forms routing information tables according to the source and destination identifiers); and

Art Unit: 2444

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

storing a routing table created and managed by the routing unit for packet forwarding between the virtual interfaces (Page 5, paragraph [0029], where each IFM contains a virtual identifier table for each of its ports).

Foster does not expressly teach that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Foster. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central

Art Unit: 2444

routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

14. As per claim 28, Foster teaches a computer-readable storage for controlling a computer, comprising a computer program for maintaining a routing table (abstract), including computer executable instructions which, when executed by the computer, cause the computer to perform:

creating and managing virtual interfaces on a router control device according to corresponding network interfaces of a forwarder, each of the virtual interfaces having address information that is associated with one of the network interfaces of the forwarder (Page 5, paragraph [0029], where the IFM maintains a virtual identifier table for each of its ports);

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

generating a routing table for the forwarder based on routing information in routing information packets received at the network interface of the forwarder and transferred by the forwarder to the router control device (Figures 2B and 2C and accompanying description beginning page 5, paragraph [0032], where the device

Art Unit: 2444

forms routing information tables according to the source and destination identifiers); and

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

storing a routing table created and managed by the routing unit for packet forwarding between the virtual interfaces (Page 5, paragraph [0029], where each IFM contains a virtual identifier table for each of its ports).

Foster does not expressly teach that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Foster. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a

Art Unit: 2444

network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

15. As per claim 32, Dalton teaches a method performed by a processor of controlling a router, comprising:

connecting a router control device to a forwarder through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device);

creating and managing interfaces, each having address information that is associated with one of a plurality of network interfaces of the forwarder, on the router control device (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device); and

outputting (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device)

Dalton does not teach a specific rule or routing scheme to use with the firewall, only references a general set of rules. Foster teaches a system that uses virtual identifiers to process data routed through a network wherein the packet control device includes:

a virtual interface that has address information associated with the network interface of the packet forwarder (page 5, paragraph [0029], where the virtual

Art Unit: 2444

identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN);

a transmitted packet reception unit that receives the routing information packet and that associates the routing information packet with the virtual interface (Figure 3, Virtual Identifier Translation Table 325).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a virtual routing table such as that Foster teaches in the system of Dalton.

Dalton generally teaches that the central routing authority oversees packet transfer over



Art Unit: 2444

local gateways. One way of rerouting packets involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Dalton's system, as it would allow the central authority to work with another layer of security and simplicity, as well as the ability to work on various network types.

16. Claims 1-9, 12-15, 18, and 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over US 2003/0204618, Foster et al, US 6 496 935, Fink et al and WO 99/14931, Dalton et al.

17. As per claim 1, Fink teaches a packet control system (abstract) comprising:  
a packet forwarder that transfers a packet received from a network interface to another network interface (Figure 1, pre-filtering module); and  
a packet control device that routes the packet using a routing process (Figure 1, firewall 18, where the routing information is filter information), wherein  
the packet forwarder includes

a received packet transfer unit that transmits to the packet control device a routing information packet received from the network interface (Column 6, line 65 to column 7, line 16, where the firewall receives the packet and determines whether the packet should be permitted to enter and/or leave the network), and wherein

the packet control device includes

a transmitted packet reception unit that receives the routing information packet (Column 6, line 67, where the firewall inspects the packets, which

Art Unit: 2444

thereby have been transferred from the pre-filtering module to the firewall), that associates the routing information packet with the interface (Column 7, lines 2-4, where the firewall determines if the connection should be permitted to pass through the device interface), and that delivers the routing information packet to the routing process (Column 7, lines 1-4, where the analysis module performs the determination); and a transmitted packet transfer unit that receives the routing information packet sent by the routing process, and that transmits the routing information packet to the packet forwarder (Column 7, lines 17-21, where the firewall passes the relevant instructions concerning the packet to the pre-filtering module).

Fink does not teach a specific rule or routing scheme to use with the firewall, only references a general set of rules. Foster teaches a system that uses virtual identifiers to process data routed through a network wherein the packet control device includes:

a virtual interface that has address information associated with the network interface of the packet forwarder (page 5, paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined

dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

a transmitted packet reception unit that receives the routing information packet and that associates the routing information packet with the virtual interface (Figure 3, Virtual Identifier Translation Table 325).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a virtual routing table such as that Foster teaches in the firewall system of Fink. Fink teaches that the analysis module of the firewall determines actions to take with the packet, including that of rewriting address fields (Column 7, line 11). One way of rewriting addresses involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Fink's system, as it would allow the firewall to work with another layer of security and simplicity, as well as the ability to work on various network types.

Art Unit: 2444

Neither Fink nor Foster expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Fink or Foster. Fink's system generally allows for a device to filter and process packets. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

18. As per claim 2, Fink teaches a packet control device which constructs a routing table for a packet forwarder controlled by the packet control device, using a routing process running on the packet control device, the packet control device comprising:

a transmitted packet reception unit that receives the routing information packet transmitted from the packet forwarder (Column 6, line 67, where the firewall inspects the packets, which thereby have been transferred from the pre-filtering

Art Unit: 2444

module to the firewall), that associates the routing information packet with the interface corresponding to an incoming network interface of the packet forwarder (Column 7, lines 2-4, where the firewall determines if the connection should be permitted to pass through the device interface), and that transmits the routing information packet to the routing process (Column 7, lines 1-4, where the analysis module performs the determination); and

a transmitted packet transfer unit that receives the routing information packet sent by the routing process, and that transmits the routing information packet to the packet forwarder (Column 7, lines 17-21, where the firewall passes the relevant instructions concerning the packet to the pre-filtering module).

Fink does not teach a specific rule or routing scheme to use with the firewall, only references a general set of rules. Foster teaches a system that uses virtual identifiers to process data routed through a network wherein the packet control device includes:

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network

Art Unit: 2444

manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

a virtual interface that has address information associated with the network interface of the packet forwarder (page 5, paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a virtual routing table such as that Foster teaches in the firewall system of Fink. Fink teaches that the analysis module of the firewall determines actions to take with the packet, including that of rewriting address fields (column 7, line 11). One way of rewriting addresses involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Fink's system, as it would allow the firewall to work with another layer of security and simplicity, as well as the ability to work on various network types.

Neither Fink nor Foster expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Fink or Foster. Fink's system generally allows for a device to filter and process packets. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

19. As per claim 3, Fink further teaches:

a routing table transfer unit that acquires a routing table updated by the routing process, and that transmits the routing table to the packet forwarder (column 4, lines 51-55, where the firewall sends packet passage information to the pre-filtering module, which allows for forwarding and routing by the forwarder).

20. As per claim 4, Fink teaches a packet control device which constructs a routing table for a packet forwarder controlled by the packet control device which determines an outgoing network interface of the packet received at an incoming network interface of the packet forwarder (column 5, lines 47-59, where the rule base establishes forwarding

Art Unit: 2444

rules for packets, permitting them to be forwarded through to the output interface or dropping them if they violate the rules of the rule base), the packet control device comprising:

a plurality of network interfaces (column 7, lines 28-32, where the pre-filtering module features a plurality of network interfaces).

Fink does not teach a specific rule or routing scheme to use with the firewall, only references a general set of rules. Foster teaches a system that uses virtual identifiers to process data routed through a network wherein the packet control device includes:

a plurality of virtual interfaces each having address information that is associated with one of the network interfaces of the packet forwarder (page 7, paragraph [0044], where the computing device uses virtual identifiers when transmitting and receiving data communications), the network interfaces of the packet control device and the virtual interfaces being divided into a plurality of groups (page 5, paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN), wherein

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);



registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

the packet control device routes the packet using a routing process associated with each of the groups considering interfaces belongs to the groups to create a dedicated routing table for each, the each of the groups corresponds to a separate device (Figures 2B and 2C, where the virtual and real addresses are kept separately and routed accordingly).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a virtual routing table such as that Foster teaches in the firewall system of Fink. Fink teaches that the analysis module of the firewall determines actions to take with the packet, including that of rewriting address fields (column 7, line 11). One way of rewriting addresses involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Fink's system, as it would allow the firewall to work with another layer of security and simplicity, as well as the ability to work on various network types.

Art Unit: 2444

Neither Fink nor Foster expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Fink or Foster. Fink's system generally allows for a device to filter and process packets. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

21. As per claim 5, Foster further teaches wherein the virtual interfaces are grouped for each packet forwarder, and the packet control device maintains routing tables using a routing process associated with each of the virtual interfaces grouped (Figures 2B and 2C, where each table uses different routing processes to make connections).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include separate routing tables for virtual and real addresses. Fink teaches that the

Art Unit: 2444

analysis module of the firewall determines actions to take with the packet, including that of rewriting address fields (column 7, line 11). One way of rewriting addresses involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Fink's system, as it would allow the firewall to work with another layer of security and simplicity, as well as the ability to work on various network types.

22. As per claim 6, Fink teaches a packet forwarder which forwards a packet from its network interface to its other network interface according to its routing table that makes a destination address of a packet associate with a next transfer destination (Column 5, lines 51-54, where the system routes according to filtering rules), comprising a received packet transfer unit that transmits a routing information packet received at the network interface to a packet control device that maintains the routing table of the packet forwarder using a routing process that generates the routing table based on routing information on the packet received at the network interface (column 9, lines 1-16, where the pre-filtering module receives packets from an external source, such as a MAC interface, and forwards the packet to the firewall through the firewall interface).

Fink does not teach a specific rule or routing scheme to use with the firewall, only references a general set of rules. Foster teaches a system that uses virtual identifiers to process data routed through a network wherein the packet control device includes:

a virtual interface that has address information associated with the network interface of the packet forwarder (page 5, paragraph [0029], where the virtual

Art Unit: 2444

identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

a transmitted packet reception unit that receives the routing information packet and that associates the routing information packet with the virtual interface (Figure 3, Virtual Identifier Translation Table 325).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a virtual routing table such as that Foster teaches in the firewall system of Fink. Fink teaches that the analysis module of the firewall determines actions to take

Art Unit: 2444

with the packet, including that of rewriting address fields (Column 7, line 11). One way of rewriting addresses involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Fink's system, as it would allow the firewall to work with another layer of security and simplicity, as well as the ability to work on various network types.

Neither Fink nor Foster expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Fink or Foster. Fink's system generally allows for a device to filter and process packets. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

Art Unit: 2444

23. As per claim 7, Fink further teaches a routing table setting unit that receives the routing table from the packet control device, and that sets the routing table to the packet forwarder (Column 7, line 62 through column 8, line 3, where the pre-filtering module contains a connection database which stores in its memory instructions from the firewall).

24. As per claim 8, Fink teaches a method of maintaining a routing table using a routing process (abstract, where the pre-filtering module performs a limited set of actions with packets previously permitted by the firewall), the method comprising:

receiving a routing information packet which is received by a packet forwarder (column 8, lines 12-15, where the pre-filtering module sends information to the firewall for processing);

delivering the routing information packet to the routing process (column 6, line 65 through column 7, line 3, where the firewall passes the packet to the analysis module for determination of whether the packet is allowed);

receiving the routing information packet sent by the routing process (column 7, lines 17-21, where the firewall forwards the relevant instructions to the pre-filtering module, inherently receiving them from the analysis module for forwarding); and

transmitting the routing information packet to the packet forwarder for transmitting from its network interface (column 7, lines 17-21, where the firewall forwards the relevant instructions for the packet to the pre-filtering module).

Art Unit: 2444

Fink does not teach a specific rule or routing scheme to use with the firewall, only references a general set of rules. Foster teaches a system that uses virtual identifiers to process data routed through a network wherein the packet control device includes:

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

associating the routing information packet with a virtual interface that has address information associated with a network interface of the packet forwarder (page 5, paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN).

Art Unit: 2444

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a virtual routing table such as that Foster teaches in the firewall system of Fink. Fink teaches that the analysis module of the firewall determines actions to take with the packet, including that of rewriting address fields (Column 7, line 11). One way of rewriting addresses involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Fink's system, as it would allow the firewall to work with another layer of security and simplicity, as well as the ability to work on various network types.

Neither Fink nor Foster expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Fink or Foster. Fink's system generally allows for a device to filter and process packets. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central



Art Unit: 2444

routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

25. As per claim 9, Fink further teaches:

acquiring a routing table updated by the routing process (column 6, line 65 through column 7, line 21, where the analysis module makes determinations, which are passed on by the firewall to the pre-filtering module); and transmitting the routing table to the packet forwarder (column 7, line 62 through column 8, line 3, where the pre-filtering module contains a connection database which stores in its memory instructions from the firewall).

26. As per claim 12, Fink teaches a method of maintaining a routing table of a packet forwarder (Column 7, line 62 through column 8, line 3, where the pre-filtering module contains a connection database which stores in its memory instructions from the firewall), the method comprising:

receiving a routing information packet from a network interface of a packet forwarder (Figure 1, where packets enter and leave the gateway through network interfaces before they are processed by the pre-filtering module and the firewall, also column 9, lines 1-16, where the pre-filtering module receives packets from an external source); and transferring the routing information packet to a packet control device, wherein the routing table makes a destination address of a packet associate with a next transfer destination (Column 6, line 65 to column 7, line 16, where the firewall

Art Unit: 2444

receives the packet and determines whether the packet should be permitted to enter and/or leave the network, also column 9, lines 1-16, where the pre-filtering module receives packets from an external source and forwards the packet to the firewall through the firewall interface).

Fink does not teach a specific rule or routing scheme to use with the firewall, only references a general set of rules. Foster teaches a system that uses virtual identifiers to process data routed through a network wherein the packet control device includes:

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

Art Unit: 2444

associating the routing information packet with a virtual interface that has address information associated with a network interface of the packet forwarder (page 5, paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a virtual routing table such as that Foster teaches in the firewall system of Fink. Fink teaches that the analysis module of the firewall determines actions to take with the packet, including that of rewriting address fields (Column 7, line 11). One way of rewriting addresses involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Fink's system, as it would allow the firewall to work with another layer of security and simplicity, as well as the ability to work on various network types.

Neither Fink nor Foster expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Fink or Foster. Fink's

Art Unit: 2444

system generally allows for a device to filter and process packets. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

27. As per claim 13, Fink further teaches:

receiving the routing table from a packet control device (Column 6, line 65 through column 7, line 3, where the firewall passes the packet to the analysis module for determination of whether the packet is allowed); and  
setting the routing table to the packet forwarder (Column 7, lines 17-21, where the relevant instructions for the packet are passed from the firewall to the pre-filtering module).

28. As per claim 14, Fink teaches a computer-readable storage for controlling a computer, comprising a computer program for routing a packet using a routing process, including computer executable instructions which, when executed by the computer (Column 3, line 63 through column 4, line 6, where the method can be implemented as software), cause the computer to perform:

receiving a routing information packet from a network interface of a packet forwarder (Figure 1, where packets enter and leave the gateway through network interfaces before they are processed by the pre-filtering module and the firewall);

Art Unit: 2444

transmitting the routing information packet to a packet control device (Column 6, line 65 to column 7, line 16, where the firewall receives the packet and determines whether the packet should be permitted to enter and/or leave the network);

receiving the routing information packet from the packet forwarder (Figure 3, step 4b, where the packet is received by firewall from pre-filtering module);

transmitting the routing information packet to the routing process (column 6, line 65 through column 7, line 3, where the firewall passes the packet to the analysis module for determination of whether the packet is allowed);

receiving the routing information packet transmitted from the routing process (column 7, lines 17-21, where the firewall forwards the relevant instructions to the pre-filtering module, inherently receiving them from the analysis module for forwarding); and

transmitting the routing information packet to the packet forwarder (column 7, lines 17-21, where the firewall forwards the relevant instructions for the packet to the pre-filtering module).

Fink does not teach a specific rule or routing scheme to use with the firewall, only references a general set of rules. Foster teaches a system that uses virtual identifiers to process data routed through a network wherein the packet control device includes:

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network

(paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

associating the routing information packet with a virtual interface that has address information associated with the network interface (page 5, paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a virtual routing table such as that Foster teaches in the firewall system of Fink. Fink teaches that the analysis module of the firewall determines actions to take with the packet, including that of rewriting address fields (Column 7, line 11). One way of rewriting addresses involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Fink's system, as it would allow the

Art Unit: 2444

firewall to work with another layer of security and simplicity, as well as the ability to work on various network types.

Neither Fink nor Foster expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Fink or Foster. Fink's system generally allows for a device to filter and process packets. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

29. As per claim 15, Fink further teaches the instructions further cause the computer to perform:

Art Unit: 2444

acquiring a routing table updated by the routing process (column 7, line 62 through column 8, line 3, where the pre-filtering module contains a connection database which stores in its memory instructions from the firewall); and transmitting the routing table to the packet forwarder (column 4, lines 51-55, where the firewall sends packet passage information to the pre-filtering module, which allows for forwarding and routing by the forwarder).

30. As per claim 18, Fink teaches a computer-readable storage for controlling a computer, comprising computer program for maintaining a routing table of a packet forwarder, including computer executable instructions which, when executed by the computer (Column 3, line 63 through column 4, line 6, where the method can be implemented as software), cause the computer to perform:

receiving a routing information packet from a network interface of the packet forwarder (Figure 1, where packets enter and leave the gateway through network interfaces before they are processed by the pre-filtering module and the firewall, also column 9, lines 1-16, where the pre-filtering module receives packets from an external source); and

transferring the routing information packet to the packet control device, wherein the routing table makes a destination address of a packet associate with a next transfer destination (Column 6, line 65 to column 7, line 16, where the firewall receives the packet and determines whether the packet should be permitted to enter and/or leave the network, also column 9, lines 1-16, where the pre-filtering



Art Unit: 2444

module receives packets from an external source and forwards the packet to the firewall through the firewall interface).

Fink does not teach a specific rule or routing scheme to use with the firewall, only references a general set of rules. Foster teaches a system that uses virtual identifiers to process data routed through a network wherein the packet control device includes:

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

associating the routing information packet with a virtual interface that has address information associated with the network interface (page 5, paragraph

Art Unit: 2444

[0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a virtual routing table such as that Foster teaches in the firewall system of Fink. Fink teaches that the analysis module of the firewall determines actions to take with the packet, including that of rewriting address fields (Column 7, line 11). One way of rewriting addresses involves using virtual addresses, which simplify routing, as they allow a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Fink's system, as it would allow the firewall to work with another layer of security and simplicity, as well as the ability to work on various network types.

Neither Fink nor Foster expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Fink or Foster. Fink's system generally allows for a device to filter and process packets. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a

Art Unit: 2444

network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

31. As per claim 19, Fink further teaches the instructions further cause the computer to perform:

receiving the routing table from a packet control device (Column 6, line 65 through column 7, line 3, where the firewall passes the packet to the analysis module for determination of whether the packet is allowed); and  
setting the routing table to the packet forwarder (Column 7, lines 17-21, where the relevant instructions for the packet are passed from the firewall to the pre-filtering module).

32. Claims 21-23, 25-27, and 29-31 are rejected under 35 U.S.C. 103(a) as being unpatentable over US 2003/0204618, Foster et al and WO 99/14931, Dalton et al as applied to claims 20, 24, and 28 above, and further in view of US 6 272 522, Lin et al.

33. As per claim 21, neither Foster or Dalton expressly teaches a specific method of generating or updating the routing tables for his system. Lin teaches a method of routing within a packet switching system comprising:

a tunnel transfer unit that transfers the routing information packet via a communication path that connects between the network interface and the virtual interface (Column 10, lines 17-42, where the packet is sent from the network

Art Unit: 2444

interface of the switching processor to the virtual interface of the control processor), wherein

the routing information storage unit stores the routing information in the routing information packet transferred by the tunnel transfer unit (Column 6, lines 43-54, where the raw load data is sent to the master module to determine the new load balancing), and

the routing unit generates the routing table for the forwarder based on the routing information stored in the routing information storage unit (Column 6, lines 4-6, where the control processor writes the new load balancing information into the shared memory for use by the switching processor).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a control processor for generating and updating the routing tables such as that disclosed by Lin in the routing system as taught by Foster. A central control processor Such as that in Lin allows the system to work faster, making the routing and switching able to occur more efficiently, as they can occur simultaneously (Lin, column 7, lines 18-24).

34. As per claim 22, neither Foster nor Dalton expressly teaches a specific method of generating or updating the routing tables for his system. Lin teaches a method of routing within a packet switching system comprising:

a routing table transmission unit that acquires the routing table and that transmits the routing table to the forwarder (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor), wherein

Art Unit: 2444

the routing unit generates the routing table for the forwarder based on the routing information stored in the routing information storage unit (Column 6, lines 55-60, where the switching processor accesses the routing table stored in the shared memory).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a control processor for generating and updating the routing tables such as that disclosed by Lin in the routing system as taught by Foster. A central control processor Such as that in Lin allows the system to work faster, making the routing and switching able to occur more efficiently, as they can occur simultaneously (Lin, column 7, lines 18-24).

35. As per claim 23, Lin teaches a router control system which includes a forwarder and a router control device (Figure 1, pre-filtering module and firewall), wherein the router control device includes

a tunnel transfer unit that transfers the routing information packet via a communication path that connects between the network interface and the virtual interface (Column 10, lines 17-42, where the packet is sent from the network interface of the switching processor to the virtual interface of the control processor);

a routing unit that generates the routing table for the forwarder based on the routing information stored in the routing information storage unit (Column 2, line 66, through column 3, line 3, where the control processor

Art Unit: 2444

server to generate configuration information for the switching processors);

and

the routing table transmission unit that acquires the routing table, and transmits the routing table to the forwarder (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor), and the forwarder forwards a packet from its network interface to its other network interface according to its routing table (abstract, where the switching processors route received packets through to an external network), and includes a received packet transfer unit that transmits a routing information packet received at the network interface to the router control device that maintains the routing table of the forwarder using a routing process (Column 6, lines 43-54, where the raw load data is sent to the control processor, and after the data is processed, it is written into shared memory and used by the switching processors (Column 6, lines 4-6)).

Lin does not teach a virtual interface method for use with his routing system. Foster teaches a system that routes packets using virtual identifier, where the router control device includes:

a virtual interface setting unit that that creates and manages virtual interfaces on a router control device according to corresponding network interfaces of a forwarder, each of the virtual interfaces having address information that is associated with one of the network interfaces of the forwarder (Page 5, paragraph [0029], where the IFM maintains a virtual identifier table for each of its ports);

Art Unit: 2444

a deciding unit for deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

a registering unit for registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

a transmitting unit for transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and a routing information storage unit that stores routing information in the routing information packet transferred by the tunnel transfer unit (Page 5, paragraph [0029], where each IFM contains a virtual identifier table for each of its ports).

It would have been obvious to one of ordinary skill in the art at the time of the invention to use a virtual addressing method such as that taught by Foster in the system disclosed by Lin. Lin's system effectively reroutes packets, regardless of the packet

Art Unit: 2444

type. Foster's virtual identifier method would simplify routing, as it allows a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]).

This would be beneficial in Lin's system, as it would allow the routing table to work with virtual as well as physical addresses, making it more versatile.

Neither Foster nor Lin expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Foster. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

36. As per claim 25, neither Foster nor Dalton expressly teaches a specific method of generating or updating the routing tables for his system. Lin teaches a method of routing within a packet switching system comprising:



Art Unit: 2444

transferring the routing information packet via a communication path that connects between the network interface and the virtual interface (Column 10, lines 17-42, where the packet is sent from the network interface of the switching processor to the virtual interface of the control processor), wherein

the storing includes storing the routing information in the routing information packet transferred by the tunnel transfer unit (Column 6, lines 43-54, where the raw load data is sent to the master module to determine the new load balancing), and

the generating includes generating the routing table for the forwarder based on the routing information stored (Column 6, lines 4-6, where the control processor writes the new load balancing information into the shared memory for use by the switching processor).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a control processor for generating and updating the routing tables such as that disclosed by Lin in the routing system as taught by Foster. A central control processor Such as that in Lin allows the system to work faster, making the routing and switching able to occur more efficiently, as they can occur simultaneously (Lin, column 7, lines 18-24).

37. As per claim 26, neither Foster nor Dalton expressly teaches a specific method of generating or updating the routing tables for his system. Lin teaches a method of routing within a packet switching system comprising:

Art Unit: 2444

acquiring the routing table (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor); and transmitting the routing table to the forwarder (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor), wherein

the generating includes generating the routing table for the forwarder based on the routing information stored (Column 6, lines 55-60, where the switching processor accesses the routing table stored in the shared memory).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a control processor for generating and updating the routing tables such as that disclosed by Lin in the routing system as taught by Foster. A central control processor Such as that in Lin allows the system to work faster, making the routing and switching able to occur more efficiently, as they can occur simultaneously (Lin, column 7, lines 18-24).

38. As per claim 27, Lin teaches a method of maintaining a routing table (Figure 1, pre-filtering module and firewall), comprising:

transferring the routing information packet by tunneling via a communication path that connects between the network interface and the virtual interface (Column 10, lines 17-42, where the packet is sent from the network interface of the switching processor to the virtual interface of the control processor);

Art Unit: 2444

generating a routing table for the forwarder based on the routing information stored (Column 2, line 66, through column 3, line 3, where the control processor server to generate configuration information for the switching processors);

acquiring the routing table (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor);

transmitting the routing table to the forwarder (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor);

forwarding a packet from a network interface of the forwarder to other network interface of the forwarder according to a routing table of the forwarder (abstract, where the switching processors route received packets through to an external network); and

transmitting a routing information packet received at the network interface of the forwarder to the router control device that maintains the routing table of the forwarder using a routing process (Column 6, lines 43-54, where the raw load data is sent to the control processor, and after the data is processed, it is written into shared memory and used by the switching processors (Column 6, lines 4-6)).

Lin does not teach a virtual interface method for use with his routing system. Foster teaches a system that routes packets using virtual identifier, where the router control device includes:

creating and managing virtual interfaces on a router control device according to corresponding network interfaces of a forwarder, each of the virtual interfaces

Art Unit: 2444

having address information that is associated with one of the network interfaces of the forwarder (Page 5, paragraph [0029], where the IFM maintains a virtual identifier table for each of its ports);

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029], where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and

storing routing information on the routing information in the routing information packet transferred (Page 5, paragraph [0029], where each IFM contains a virtual identifier table for each of its ports).

It would have been obvious to one of ordinary skill in the art at the time of the invention to use a virtual addressing method such as that taught by Foster in the system

Art Unit: 2444

disclosed by Lin. Lin's system effectively reroutes packets, regardless of the packet type. Foster's virtual identifier method would simplify routing, as it allows a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Lin's system, as it would allow the routing table to work with virtual as well as physical addresses, making it more versatile.

Neither Foster nor Lin expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Foster. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

Art Unit: 2444

39. As per claim 29, neither Foster nor Dalton expressly teaches a specific method of generating or updating the routing tables for his system. Lin teaches a method of routing within a packet switching system wherein:

instructions further cause the computer to perform transferring the routing information packet via a communication path that connects between the network interface and the virtual interface (Column 10, lines 17-42, where the packet is sent from the network interface of the switching processor to the virtual interface of the control processor), wherein the storing includes storing the routing information in the routing information packet transferred by the tunnel transfer unit (Column 6, lines 43-54, where the raw load data is sent to the master module to determine the new load balancing), and the generating includes generating the routing table for the forwarder based on the routing information stored (Column 6, lines 4-6, where the control processor writes the new load balancing information into the shared memory for use by the switching processor).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a control processor for generating and updating the routing tables such as that disclosed by Lin in the routing system as taught by Foster. A central control processor Such as that in Lin allows the system to work faster, making the routing and switching able to occur more efficiently, as they can occur simultaneously (Lin, column 7, lines 18-24).

Art Unit: 2444

40. As per claim 30, neither Foster nor Dalton expressly teaches a specific method of generating or updating the routing tables for his system. Lin teaches a method of routing within a packet switching system wherein:

the instructions further cause the computer to perform:

acquiring the routing table (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor);

and

transmitting the routing table to the forwarder (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor), wherein

the generating includes generating the routing table for the forwarder based on the routing information stored (Column 6, lines 55-60, where the switching processor accesses the routing table stored in the shared memory).

It would have been obvious to one of ordinary skill in the art at the time of the invention to include a control processor for generating and updating the routing tables such as that disclosed by Lin in the routing system as taught by Foster. A central control processor Such as that in Lin allows the system to work faster, making the routing and switching able to occur more efficiently, as they can occur simultaneously (Lin, column 7, lines 18-24).

41. As per claim 31, Lin teaches a computer-readable storage for controlling a computer, comprising a computer program for maintaining a routing table, including

Art Unit: 2444

computer executable instructions stored on a computer readable medium, wherein the instructions, when executed by the computer, cause the computer to perform:

transferring a routing information packet by tunneling via a communication path that connects between the network interface and the virtual interface (Column 10, lines 17-42, where the packet is sent from the network interface of the switching processor to the virtual interface of the control processor);

generating a routing table for the forwarder based on the routing information stored (Column 2, line 66, through column 3, line 3, where the control processor server to generate configuration information for the switching processors);

acquiring the routing table (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor);

transmitting the routing table to the forwarder (Column 6, lines 4-6, where the distribution data is written into the shared memory for use by the switching processor);

forwarding a packet from a network interface of the forwarder to another network interface of the forwarder according to a routing table of the forwarder (abstract, where the switching processors route received packets through to an external network); and

transmitting a routing information packet received at the network interface of the forwarder to the router control device that maintains the routing table of the forwarder using a routing process (Column 6, lines 43-54, where the raw load



Art Unit: 2444

data is sent to the control processor, and after the data is processed, it is written into shared memory and used by the switching processors (Column 6, lines 4-6)).

Lin does not teach a virtual interface method for use with his routing system. Foster teaches a system that routes packets using virtual identifier, where the router control device includes:

creating and managing virtual interfaces on a router control device according to corresponding network interfaces of a forwarder, each of the virtual interfaces having address information that is associated with one of the network interfaces of the forwarder (Page 5, paragraph [0029], where the IFM maintains a virtual identifier table for each of its ports);

deciding on, according to a routing protocol, a path to be selected based on information of the network interface and routing information which the packet control device exchanges with the other packet control device in a network (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path);

registering the path by the deciding to a routing table (paragraphs 16-17, where the path for the packet to be sent may be determined dynamically by the network manager, and each device may be configured along the path to be notified of the virtual path); and

transmitting the packet to the packet forwarder including the network interface that is associated with an address of the virtual interface (paragraph [0029],

Art Unit: 2444

where the virtual identifier translation table reflects the IP ports related to the virtual interfaces of the VPN); and  
storing routing information on the routing information in the routing information packet transferred (Page 5, paragraph [0029], where each IFM contains a virtual identifier table for each of its ports);

It would have been obvious to one of ordinary skill in the art at the time of the invention to use a virtual addressing method such as that taught by Foster in the system disclosed by Lin. Lin's system effectively reroutes packets, regardless of the packet type. Foster's virtual identifier method would simplify routing, as it allows a path to be reconfigured in a manner transparent to a source (Foster, page 3, paragraph [0019]). This would be beneficial in Lin's system, as it would allow the routing table to work with virtual as well as physical addresses, making it more versatile.

Neither Foster nor Lin expressly teaches that the packet forwarder and the routing device are located in separate networked devices. Dalton teaches a routing engine wherein:

the packet forwarder is connected to the packet routing control device through a network (page 22, lines 1-23, where the routing engine processes and returns a request for route information to a packet routing device).

It would have been obvious to one of ordinary skill in the art at the time of the invention to utilize a packet controller separate from the packet forwarder such as taught by Dalton in a packet forwarding system such as that taught by Foster. Foster's system allows a packet forwarder to create virtual channels for a packet to travel through a

Art Unit: 2444

network. In both systems, the device is required to route packets to a device through a network. Dalton's system benefits any forwarding system, as it provides a central routing authority, such that routing may be offloaded from the local gateways, allowing the system to function with a greater ability to meet set parameters (page 2, lines 13-23).

### ***Conclusion***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to THOMAS RICHARDSON whose telephone number is (571) 270-1191. The examiner can normally be reached on Monday through Thursday, 8am-5pm EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, William Vaughn can be reached on (571) 272-3922. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Application/Control Number: 10/781,792

Page 59

Art Unit: 2444

/TAMMY THANH NGUYEN/

Primary Examiner, Art Unit 2444

TR